

ATKINS



Modeling Potential Circulation Improvements in Old Tampa Bay

Tampa, FL

February 8, 2018

Todd DeMunda, P.E.


Shayne Paynter, Ph.D., P.E., P.G.

Mike Salisbury, P.E.




Project Location

Old Tampa Bay
Tampa, FL



Project Location

Old Tampa Bay
Tampa, FL

 area of interest



Background

- Florida Department of Transportation (FDOT) anticipating significant costs with upcoming local construction and associated runoff treatment
- Department of Environmental Protection encouraging alternatives to wet detention ponds for treatment
- Area of concern in Old Tampa Bay north of the Courtney Campbell Causeway (SR60)
- Location of healthy seagrass beds in the 1930s prior to causeway construction

Background

- Phase I of this study determined that a modification of the Causeway (adding a bridge section to increase flow exchange) would likely bring about an ecological response greater than that achieved by additional runoff treatment
- Phase II involved the development and application of a hydrodynamic model to quantify the changes in circulation and residence time achieved by adding bridge segment

Methodology

- Field data collection (water levels, currents) during August-September 2015
- Bathymetric survey in area of interest
- Delft3D hydrodynamic model
 - Tidal and wind forcing
 - Coarse and nested regional and local model grids
 - Conservative constituent dispersion
 - Quantify changes in residence time with modification to the Causeway

Model Development

Delft3D-FLOW hydrodynamic model


- Regional domain encompassing Tampa Bay to the Gulf of Mexico
 - Based on NOAA's Tampa Bay Operational Forecast System model
- Nested domain in area of interest driven by regional model
 - Uniform 10 m spatial resolution

Model Development


Delft3D-FLOW hydrodynamic model

- Spatially-varying tidal forcing at Gulf of Mexico
 - Constituents from Oregon State University Tidal Model Driver (TMD)
- Uniform wind forcing from measured data at NOAA Station 8726607
- Daily precipitation from Tampa International Airport (KTPA)
 - (over model domain only; no stormwater runoff into domain)
- Model run concurrent with field data collection period


Regional Grid



Nested Grid



Proposed Bridge Location

 60 m (200 ft)
opening

 flap-gate culverts




Modeled Scenarios


Name	Proposed Opening
Existing conditions	None (no change)
Alternative 1 200 ft opening	60 m (200 ft) width -2.3 m (-7.6 ft) NAVD88 bottom

Simulating Residence Time

- Conservative, neutrally-buoyant, generic tracer in model
- Start with uniform 1 kg/m³ in area of interest
- Run model for 1 week, compare initial & final concentrations in area of interest between the 2 alternatives




Results – Existing Conditions







Results – 60 m Opening


Western area
of interest:
concentrations
drop below 50%
of initial level 2
days faster

Eastern area
of interest:
concentrations
drop below 50%
of initial level 1.5
days faster



Reduction in Residence Time

-  Stratum A
-  Stratum B
-  Stratum C
-  Bridge location



Conclusions

- Relief bridge effective in increasing exchange between area of interest and greater Tampa Bay
- Allows for freshwater runoff to be more readily dispersed, increasing salinity in the area
- Help return hydrodynamic conditions to pre-causeway historical conditions
- Gradually restore seagrass population to historical healthy condition


Conclusions

- Construction currently underway, completion Summer 2019



Further
Work in
Tampa
Bay:

Cooper's
Bayou




Overview

- Previous work inspired new investigations elsewhere
- Build upon 2017 study focused on stormwater runoff
- Increase circulation in historic seagrass areas in western OTB
- Use same methodology as before (generic tracers) to track water originating in Cooper's Bayou and surrounding waters

Model Domain

- Based on work from a 2017 study
- Three grids (coarse, medium, fine) using Delft3D's domain decomposition




Model setup

- Grid encompassing Old Tampa Bay, with increasing spatial detail within Cooper's Bayou
- Bathymetry from previous model
- Tidal boundary at Gandy Bridge
- Five model scenarios
- Residence time defined as the time to reach 10% of initial concentration of tracer (i.e. a 90% reduction)


Model scenario 1: Base conditions

- Existing conditions, plus:
 - bayou dredging to 4 ft below MSL
 - Improved mangrove channel (option 2 in previous study)
 - channel enlargement at Damascus Rd. (current project)




Model scenario 2: Eastern cut

- Base conditions, plus:
 - ~180 ft channel through the narrowest section of mangroves on the eastern side of the Bayou (circled in red)




Model scenarios 3-5: Eastern cut + SR60 opening

- Base conditions, plus:
 - ~180 ft channel through the narrowest section of mangroves on the eastern side of the Bayou (circled in red)
 - channel through SR60 east of Damascus Rd (circled in red) (800, 400, 200 ft widths tested)




Residence time, Bayou tracer, Base vs. Scenario 2

S




Scenario 1




Scenario 2

Residence time, Bayou tracer, Base vs. Scenario 3

S




Scenario 1




Scenario 3

Change in Residence time (%), Bayou tracer, vs. Base

S



Scenario 2




Scenario 3

Results

Location	Scenario	Residence time (days)	Change vs. Base (%)
south bayou	Base	3.17	-
	Eastern cut	2.75	-13
	Eastern cut + SR60 opening 800 ft	2.67	-16
	Eastern cut + SR60 opening 400 ft	2.75	-13
	Eastern cut + SR60 opening 200 ft	2.75	-13
middle bayou	Base	2.75	-
	Eastern cut	2.67	-3
	Eastern cut + SR60 opening 800 ft	2.17	-21
	Eastern cut + SR60 opening 400 ft	2.08	-24
	Eastern cut + SR60 opening 200 ft	2.67	-3
north bayou	Base	2.67	-
	Eastern cut	1.67	-37
	Eastern cut + SR60 opening 800 ft	1.67	-37
	Eastern cut + SR60 opening 400 ft	1.67	-37
	Eastern cut + SR60 opening 200 ft	1.67	-37

Summary

- Two of a number of projects in Tampa Bay seeking to enhance / restore historical flow pathways



Thank you!

Questions?